



Hyperion Accent

Specification Features

| | |
|---|--|
| Input | 8VAC |
| Power Consumption | <.9W per linear foot (<2.95W per linear meter) |
| System Efficiency | >78% |
| Bending Radius | <.05" (1.27 mm) |
| Module Spacing | 2" (50.8mm) |
| Drives Up To | 8VAC Power Supply 96 - 70 feet (21.3 m) 8VAC Power Supply 24 - 25 feet (7.62 m) |
| Length | 25 feet (7.62 m) of product per reel |
| Distribution Angle | >120° (6500WHE) or >160° (6500EE, 4100EE, 3000EE) |
| Rated Life | 50,000 hours |
| Construction | High Performance Flame Retardant Polyester Film with Adhesive Backing |
| Operating Temperature | -5°F(-20°C) to 165°F(75°C) |
| Listing | ETL |
| Warranty | Limited 5 Year |
| Component Requirements (This system may require the following components to operate, please contact the factory for details) | Power Supply - HRLA-96 or HRLA-24 HRLA-HC Power Connector Kit HRLA-JC Jumper Connector Kit HRLA-SC-P Support Clamps |



Key Features

- The only LED system in the industry with Replaceable LED modules
- Dimmable
- Available in 8 colors
- Highly flexible strip which adheres to any surface

Applications

- Accent Lighting
- Display Lighting
- Cove Lighting



Hyperion Accent